



**P.O. Box 8, Old Bethpage, NY 11804**  
**Office: (631) 249-7471 Fax: (631) 249-9036**

## Recommended Quantities and Instructions for Use

### Stadium Red™, Custom Clay and Custom Classic Infield Mixes

	<b>New Construction 3" Overall</b>	<b>Resurface 1" Layer</b>
Regulation Field, Grass Infield	140 Tons	50 Tons
Regulation Field, Skinned Infield	200 Tons	75 Tons
Little League, Grass Infield	35 Tons	15 Tons
Little League, Skinned Infield	75 Tons	25 Tons
Softball Field, 50' Radius	75 Tons	25 Tons

**New Construction:** Spread material over good drainage base for optimum playability. Apply 3" on base paths with 6" near bases to insure safe sliding. Laser guided equipment is preferred in spreading the material. If dry, moisten evenly; fill in low spots, and power roll. Drag mat until smooth. After installation, maintain with drag mat.

**Resurfacing:** Grade and scarify infield to prepare new infield mix. Apply necessary quantity, spread, drag and power roll. If existing infield drains poorly, Gridtec Drainage System can be installed. Our Infield Mixes will provide good surface drainage with good traction.

### Gametime Athletic Field Conditioner/Absorbent

	<b>Bulk</b>	<b>Bags</b>
Regulation Field, Grass Infield	12 Tons	480
Regulation Field, Skinned Infield	14 Tons	560
Little League, Grass Infield	5 Tons	200
Little League, Skinned Infield	6 Tons	240
Softball Field, 50' Radius	10 Tons	400

This material helps condition infields to reduce compaction and also helps alleviate puddling areas. Conditioning the field maximizes performance and safety.

Installation Instructions:

Moisten skin area to loosen surface.  
 Spread Gametime over the infield (amounts based on grid above for complete conditioning), concentrating on the traffic and problem areas.  
 Then use nail drag or hand rake to rake in the material.